

# TECHBIND-P

*An efficient binder for a pelletized aquafeed*



## PROPERTIES

Pellets that break down easily during handling, storage, transportation and in the water lead to financial loss of nutritional ingredients and also pollute the rearing media, creating favourable conditions for pathogen development. **TECHBIND-P** reduces these financial losses and pathogen risks

- **TECHBIND-P** produces strong durable but flexible enough to be eaten pellets
- **TECHBIND-P** requires no special operating procedures.
- **TECHBIND-P** requires a low inclusion rate in feed formula thus improving your lowest cost feed and increasing nutrient content of rations. It reduces handling and labor problems, associated with the extra volume and inconvenience of handling many high inclusion binders.

*TECHBIND is recommended for use with high fat and/or extruded feeds.*

## COMPOSITION

- All ingredients contained in **TECHBIND-P** are in conformity with EEC and FDA feedingstuffs regulations :
  - ✓ modified lignosulphonate
  - ✓ modified starches
  - ✓ edible fatty acids

## USE AND PRESENTATION

- Use at the rate of 1-2 kg per ton of finished feed.
- Should be added after the vitamins and other micro-ingredients are added
- Follow general pelleting guidelines that recommend applying the maximum amount of steam in the conditioning chamber and corresponding production rates, to produce the best quality pellets.
- Stability : stable for 1 year when in sealed bags.
- Storage : store in cool dry place, out of direct sunlight.
- Hazard identification : n.a.

